

Performance Data

Model	Power		Caliber	Q (m ³ /h)	1	1.2	1.6	2	2.4	2.8	3.2	Head Range (m)	Packing Dim. (L×W×H) mm	G.W.(kg)	
	kW	HP												BL	BLT
BL(T)2-2	0.37	0.5	DN25 (1 1/4')	H (m)	18	17	16	15	13	12	10	10~18	590×330×320	25	30
BL(T)2-3	0.37	0.5			27	26	24	22	20	18	15	15~27	590×330×320	25	30
BL(T)2-4	0.55	0.75			36	35	33	30	26	24	20	20~36	630×330×320	28	32
BL(T)2-5	0.55	0.75			45	43	40	37	33	30	24	24~45	630×330×320	28	33
BL(T)2-6	0.75	1			53	52	50	45	40	36	30	30~53	730×330×320	32	37
BL(T)2-7	0.75	1			63	61	57	52	47	41	35	35~63	730×330×320	32	37
BL(T)2-9	1.1	1.5			80	78	73	67	61	54	45	45~80	790×330×320	35	40
3L(T)2-11	1.1	1.5			98	95	89	82	73	64	54	54~98	790×330×320	36	41
3L(T)2-13	1.5	2			116	114	106	98	89	78	65	65~116	840×330×320	40	45
3L(T)2-15	1.5	2			134	130	123	112	100	90	73	73~134	880×330×320	41	46
3L(T)2-18	2.2	3			161	157	148	136	121	108	91	91~161	930×330×320	46	51
3L(T)2-22	2.2	3			197	192	180	165	148	130	110	110~197	1030×330×440	49	54
3L(T)2-26	3	4			232	228	214	198	179	158	130	130~232	1100×330×440	58	62